TX HMI/PLC Series
Plug-In Module
RS232 Interface
TX-RS232

Type	TX-RS232
ID	100002599
Supply	
System power supply	From the HMI
System data	
Fieldbus connection technology	1 × 9-pol D-SUB, Female connector
Electrical isolation	no
Standard/Directive conformity	
Approvals and certificates	CE, cULus
General Information	
Dimensions (W x L x H)	41.2 x 90.3 x 23.8 mm
Ambient temperature	-20…+60 °C
Storage temperature	-20…+70 °C
Relative humidity	5…85 %, non-condensing
Protection class	IP20
Housing material	Metal
Housing color	Silver
Mounting	On HMIs of the TX500 and TX700 series

- Plug-in extension module for use with HMIs of the TX700 and TX800 product series
- RS232 interface
- 9-pin SUB-D female connector
- With plug-in extension slot

Edition • 2025-02-26T11:59:00+01:00

Connection and pin assignment

	**Serial Interface** SUB-D female connector, 9-pin	Pin Assignment RS232  1 = GND 2 = n.c. 3 = TX 4 = RX 5 = n.c. 6 = +5 V output 7 = CTS 8 = RTS 9 = n.c.
	**Port for Plug-in Module** The expansion slot can be used for another plug-in module. The possible module combinations are described in the manual for the base units.	.

Edition • 2025-02-26T11:59:00+01:00